

# BEE - USB Pro audio interface 2 kanaler



## 2-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB Type-C port, compatible with USB 3.0, (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- Sampling rate: up to 192 kHz max., 24 bits
- 2 mono input channels via comb. jacks (XLR/6.3 mm jack), balanced, switchable line/instrument
- Main output, switchable mono/stereo
- Low cut function
- Switchable direct monitoring
- 1 x 6.3 mm jack output L/R
- Adjustable 6.3 mm headphone output
- +48 V phantom power, can be activated for each channel
- LED peak indication for each channel
- Robust metal housing of compact size, brushed aluminium front panel, black anodised
- Separate USB Type-C input, DC 5 V, for external power supply (not included in the scope of delivery)

System requirements: Windows 10/11, Mac OS, iOS, Linux

## Technical data:

Input channels	: -
Number of mix/mono	: -
No. of stereo	: -
No. of channels	: 2
No. of inputs	: 4
Mic input	: 2.5 mV, 2 x comb. XLR/6.3 mm (line/mic), bal. 1.4 kOhm
Line input	: 19 mV, 2 x comb. XLR/6.3 mm (line/mic), bal. 10.5 kOhm (line)/500 kOhm (inst.)
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 6.5 V max., 2 x 6.3 mm jack L/R
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 1 x 6.3 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: yes, USB Type-C (compatible with USB 3.0), full-duplex
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.001%
S/N ratio	: ≥ 87 dBu
Crosstalk	: ≥ 55 dB
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
equalizer	: -

Talkover	: -
Phantom power	: +48 V
Crossfader	: -
Media player	: -
Amplifier	: -
Power supply	: via USB interface DC 5 V/1,250 mA
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Operating voltage (possible alternative)	: DC 5 V
Power supply (possible alternative)	: 1,250 mA
Admiss. ambient temp.	: 0-40 °C
Width	: 190 mm
Height	: 40 mm
Depth	: 117 mm
Rack units, RU	: -
Weight	: 717 g
Packing dimensions (W x H x L)	: 0.18 x 0.062 x 0.236 m
Gross weight	: 1.017 kg
Net weight	: 0.725 kg