

## ETS-215/WS - PA Speaker Column



PA column speaker,  
in an extruded aluminium cabinet, with top and bottom plates of aluminium.

- 100 V line technique
- 5-step power selector switch
- 2 x M6 threaded bushing
- Metal front grille
- Supplied with mounting bracket
- Connection via cable, 2 cores

## Technical data:

100 V	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 15/7.5/3.75/2 W
Impedance	: -
Frequency range	: 250-15,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 4
Speaker size	: -
SPL	: 92 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: aluminium
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 105 x 405 x 85 mm
Width	: 105 mm
Height	: 405 mm

Depth	: 85 mm
Weight	: 2.5 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.13 x 0.47 x 0.15 m
Gross weight	: 2.82 kg
Net weight	: 2.5 kg