

TS-C10-300/T - PA Speaker Column



Weatherproof PA column speaker,
with EN 54-24 certification.

- 100 V line technique
- 2 x 7.7 cm (3") waterproof full range speaker
- 4 power taps: 10/6/3/1.5 W
- Connection via ceramic terminals with thermal fuse in the cabinet
- 2 x PG9 cable gland
- Robust, plastic-coated aluminium cabinet with front protective grille
- The speaker complies with British Standard BS 5839, part 8
- Supplied with plastic wall bracket for pivoting and tilting

Technical data:

| | |
|--------------------------------|-----------------------------|
| Outdoors | : 1 |
| weatherproof | : 1 |
| 100 V | : 1 |
| EN 54 certification | : 1 |
| Active/passive | : passive |
| Transmission technology | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 10/6/3/1.5 W |
| Impedance | : - |
| Frequency range | : 200-18,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : 2 x 77 mm |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 2 |
| Speaker size | : - |
| SPL | : 95 dB/W/m |
| Max. rated SPL | : 104 dB |
| Radiation angle/beam angle | : H: 149°/V: 66° |
| Radiation angle, horizontal | : 149° |
| Radiation angle, vertical | : 66° |
| Features | : - |
| Housing material | : aluminium |
| Colour | : white aluminium, RAL 9006 |
| Mounting device | : wall bracket |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -20 °C to +90 °C |
| Power supply | : - |

| | |
|--------------------------------|-------------------------|
| Dimensions | : 100 x 296 x 92 mm |
| Width | : 100 mm |
| Height | : 296 mm |
| Depth | : 92 mm |
| Weight | : 1.6 kg |
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.175 x 0.19 x 0.37 m |
| Gross weight | : 2.06 kg |
| Net weight | : 1.758 kg |