

## EDL-416EN/WS - PA Loudspeaker



Moisture-proof PA ball speaker,  
with EN 54-24 certification, 1438-CPR-0535.

- 100 V transmission technology
- White ABS housing (UL 94HB), UV-resistant and weatherproof
- Moisture-proof speaker cone
- Supplied with 450 cm connection cable and canopy
- Ceramic connection terminal, thermal fuse

## Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
EN 54 certification	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 16/8/4 W
Impedance	: -
Frequency range	: 130-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 130 mm full range speaker
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 13 cm (5")
SPL	: 89.9 dB/W/m
Max. rated SPL	: 101 dB
Radiation angle/beam angle	: 196° (1 kHz)132° (2 kHz)170° (4 kHz)
 Radiation angle, horizontal	 : 196° (1 kHz)132° (2 kHz)170° (4 kHz)
 Radiation angle, vertical	 : 196° (1 kHz)132° (2 kHz)170° (4 kHz)
 Features	 : -
Housing material	: ABS
Colour	: white, RALÂ 9010
Mounting device	: canopy
Protected against ball rebound	: -
Protection class	: IP35

Admiss. ambient temp.

: -20 °C to +80 °C

Power supply

: -



Dimensions	: 185 mm x 157 mm
Width	: 185 mm
Height	: 157 mm
Depth	: -
Weight	: 1.6 kg
Inputs	: ceramic terminal with thermal fuse
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.19 x 0.18 x 0.19 m
Gross weight	: 1.79 kg
Net weight	: 1.64 kg