

# DA-10-260/T - PA Loudspeaker



The sound projector with a power capacity of 10 W is fitted with two 13 cm full range speakers and a 100 V transformer with 4 power taps. A robust plastic-coated aluminium housing in RAL9010 and a vandal-resistant aluminium mounting plate ensure a permanent installation of this speaker. The 2-pole ceramic terminal and thermal fuse as well as the waterproof speaker ensure extra operating reliability.

With the high protection class IP65, the speaker is also protected against weather influences. It is particularly suitable for the application in corridors and hallways. The speaker complies with British Standard BS 5839, Part 8.

Weatherproof PA sound projector,  
for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 2 x 13 cm full range speaker for bi-directional radiation
- 100 V transformer with power taps 10/6/3/1.5 W
- Connection via ceramic terminals with thermal fuse in the mounting base
- Robust plastic-coated aluminium housing with front protective grille
- Robust vandal-resistant aluminium mounting base

## Technical data:

|                                |                    |
|--------------------------------|--------------------|
| Outdoors                       | : 1                |
| weatherproof                   | : 1                |
| 100 V                          | : 1                |
| EN 54 certification            | : 1                |
| Active/passive                 | : passive          |
| Transmission technology        | : 100 V            |
| Total output power             | : -                |
| Power rating (RMS)             | : -                |
| Total power rating             | : -                |
| Power rating (RMS)             | : 10/6/3/1.5 W     |
| Impedance                      | : -                |
| Frequency range                | : 120-17,000 Hz    |
| THD                            | : -                |
| S/N ratio                      | : -                |
| Input signal                   | : -                |
| System                         | : -                |
| Full range speaker             | : 2 x 13 cm        |
| Bass speaker                   | : -                |
| Midrange speaker               | : -                |
| Tweeter                        | : -                |
| Number of speakers             | : 2                |
| Speaker size                   | : 13 cm            |
| SPL                            | : 93 dB/W/m        |
| Max. rated SPL                 | : 103 dB           |
| Radiation angle/beam angle     | : 150°             |
| Radiation angle, horizontal    | : 150°             |
| Radiation angle, vertical      | : 150°             |
| Features                       | : -                |
| Housing material               | : aluminium        |
| Colour                         | : white, RAL 9010  |
| Mounting device                | : mounting base    |
| Protected against ball rebound | : -                |
| Protection class               | : IP65             |
| Admiss. ambient temp.          | : -20 °C to +90 °C |
| Power supply                   | : -                |

---

|                                |                         |
|--------------------------------|-------------------------|
| Dimensions                     | : 166 x 197 x 161 mm    |
| Width                          | : 166 mm                |
| Height                         | : 197 mm                |
| Depth                          | : 161 mm                |
| Weight                         | : 2.31 kg               |
| Inputs                         | : -                     |
| Outputs                        | : -                     |
| Replacement voice coil         | : -                     |
| Other features                 | : -                     |
| Accessories                    | : -                     |
| Packing dimensions (W x H x L) | : 0.17 x 0.185 x 0.21 m |
| Gross weight                   | : 2.43 kg               |
| Net weight                     | : 2.31 kg               |