

ESP-230/WS - PA Wall Speaker



PA højttalersystem, i vejrbestandigt hvidt plastikkabinet med frontgitter i aluminium.

- 100 V teknologi
- 5 tapsætninger, 8 Ohm eller 100 V
- 2-vejs system
- Monteringsbeslag i rustfrit stål

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 100 W
Power rating (RMS)	: 30/20/10/5/2.5 W (100 V) 50 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 80-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: -
SPL	: 92 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP65
Admiss. ambient temp.	: -30 °C to +40 °C
Power supply	: -



Dimensions	: 157 x 260 x 170 mm
Width	: 157 mm
Height	: 260 mm
Depth	: 170 mm
Weight	: 1.8 kg
Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.2 x 0.29 x 0.2 m
Gross weight	: 2.276 kg
Net weight	: 2 kg