
-

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
protected against ball rebound	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 50/25/12.5 W
Impedance	: 4 Ohm
Frequency range	: 60-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: wideband bass-reflex
Full range speaker	: 13 cm (5") full range speaker
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 13 cm (5")
SPL	: 87 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: yes
Protection class	: IP45
Admiss. ambient temp.	: -10 °C to +40 °C

Power supply	: -
Dimensions	: 200 x 200 x 190 mm
Width	: 200 mm
Height	: 200 mm
Depth	: 190 mm
Weight	: 5.1 kg
Inputs	: screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.25 x 0.29 x 0.23 m
Gross weight	: 6 kg
Net weight	: 5.46 kg