
-

Technical data:

| | |
|--------------------------------|------------------------------|
| Outdoors | : 1 |
| weatherproof | : 1 |
| 100 V | : 1 |
| Low-impedance | : 1 |
| protected against ball rebound | : 1 |
| Active/passive | : passive |
| Transmission technology | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 240 W |
| Power rating (RMS) | : 120/60/30 W |
| Impedance | : 8 Ohm |
| Frequency range | : 48-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way bass-reflex |
| Full range speaker | : - |
| Bass speaker | : 20 cm (8") PA bass speaker |
| Midrange speaker | : - |
| Tweeter | : 25 mm (1") horn tweeter |
| Number of speakers | : 2 |
| Speaker size | : 20 cm (8") |
| SPL | : 96 dB/W/m |
| Max. rated SPL | : 117 dB |
| Radiation angle/beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : ABS |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : yes |
| Protection class | : IP45 |
| Admiss. ambient temp. | : -30 °C to +40 °C |

| | |
|--------------------------------|-------------------------------|
| Power supply | : - |
| Dimensions | : 240 x 430 x 250 mm |
| Width | : 240 mm |
| Height | : 430 mm |
| Depth | : 250 mm |
| Weight | : 11.42 kg |
| Inputs | : 1 x SPEAKER, screw terminal |
| Outputs | : 1 x SPEAKER, par. out |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.35 x 0.51 x 0.28 m |
| Gross weight | : 15.7 kg |
| Net weight | : 11.42 kg |