


EDL-255/WS - PA Loudspeaker

100V **8Ω**



PA sound projector

- 100 V transmission technology or 8 Ohm operation
- 6-step power selector switch for 15/8/4/2 W/off or 8 Ohm operation
- White plastic housing with pivoting mounting bracket

Technical data:

| | |
|--------------------------------|--------------------|
| 100 V | : 1 |
| Low-impedance | : 1 |
| Active/passive | : passive |
| Transmission technology | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 15/8/4/2 W |
| Impedance | : 8 Ohm |
| Frequency range | : 100-15,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : - |
| SPL | : 92 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle/beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 180 mm x 280 mm |
| Width | : 180 mm |

| | |
|--------------------------------|------------------------|
| Height | : - |
| Depth | : 280 mm |
| Weight | : 2.59 kg |
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.19 x 0.34 x 0.19 m |
| Gross weight | : 2.865 kg |
| Net weight | : 2.595 kg |