

MCR-10 - Cable Drum



Kabeltromle, med 10 m ledning.

- Lukket plastikhus
- 4 sokler m/jord
- Beskyttet mod overophedning
- Indikator for overophedning og overbelastning
- Kabelspecifikation: H05VV-F3G x 1,5 mm²
- Mål: 225 x 270 x 75 mm
- Vægt: 1,5 kg

Technical data:

| | |
|------------------------|--|
| Intended use | : Mains voltage, multi-socket power strip, reel, cable winding |
| Connectors | : 4 x earthed socket, 45°, 1 x earthed plug |
| Cable specification | : H05VV-F3G x 1.5mm ² |
| Length | : 10 m |
| Spliced | : - |
| Colour | : black |
| Internal conductor | : 3 x 1.5 mm ² |
| Material | : - |
| No. of cores | : 3 |
| Cable diameter | : - |
| Metre marking | : - |
| Minimum bending radius | : - |
| Shielding | : - |
| Shielding value | : - |
| Impedance | : - |
| Attenuation | : - |
| Capacitance | : - |
| Power rating | : 3,000 VA |
| Rated current | : - |
| Packaging | : - |
| Weight | : 1.52 kg |
| Position | : - |
| Special feature | : overheat protection |
| Other features | : - |