

WSA-24T - Wireless Speaker Adaptor



Trådløs stereosender, 2.4 GHz, til lydstreaming.

- Passer til modtager WSA-24R
- Stereo/mono switch
- LED-indikator for status og peak
- Ingen interferens takket være FHSS teknologien (Frequency Hopping Spread Spectrum)
- Analog line-indgang, 6,3 mm jackstik L/R og 3-polet XLR L/R
- Metalkabinet
- Strømforsyning medfølger

SOUNDCHECK 02/2016

"All too typical for IMG STAGELINE: the requirements of stage applications are effectively implemented."

tools4music 01/2016

"This compact solution is an excellent aid for every audio supplier ... shows itself ... as a robust and easy-to-use solution for audio streaming."

Technical data:

Frequency range	: 20-20,000 Hz
THD	: < 0.3%
Channel separation	: ± 90 dB
S/N ratio	: -
Transmitting power	: -
WLAN	: -
Bluetooth	: -
Operating range	: ? 30 m, without any obstacles
Profiles	: -
Codecs	: -
Power supply	: via incl. power supply
Width	: 130 mm
Height	: 54 mm
Depth	: 130 mm
Weight	: 470 g
Connections	: Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue
Other features	: 2.4 GHz, 25 channels, latency: 18Â ms