


## SA-130DMP - Amplifier



**Stereo forstærker**, med integreret MP3 afspiller (USB/SD), Bluetooth modtager og FM radio.

- Bluetooth modtager for trådløs tilslutning af smartphones eller tablets m.v.
- USB stik kan tilsluttes direkte
- Til SD-kort op til 32 GB (FAT16/FAT32), kan købes separat
- Justerbart mikrofon input og aux input på fronten
- Justerbart stereo line input
- Pre-amp main in, til for eksempel effektenheder, equalizere, feedback controllere
- 2-vejs tone kontrol
- Justerbart master output
- 482 mm (19") rack installation, 1 RS

## Technical data:

Bluetooth	: 1
Peak output power	: -
Power rating	: 130 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 75 W
Power rating at 8 Ohm	: 2 x 45 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 600 mV/30 kOhm (line) 2 mV/0.5 kOhm (mic) 370 mV/30 kOhm (aux) 950 mV/25 kOhm (amp in)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: $\pm 10$ dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: $\pm 10$ dB/10 kHz
S/N ratio	: $\hat{\approx} 80$ dB
Crosstalk attenuation	: $\hat{\approx} 45$ dB
THD	: $\hat{\approx} 0.1\%$
Phantom power	: -
Mains voltage	: $\approx$ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 320 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -

Power supply (possible  
alternative)

: -

Admiss. ambient temp.

: 0-40 °C

Width

: 482 mm

**MONACOR**



Height	: 44 mm
Depth	: 245 mm
Rack units, RU	: 1
Weight	: 5.62 kg
Connections	: 1 x RCA L/R (line), 1 x XLR/6.3 mm jack (mic), 1 x 3.5 mm jack (aux), 1 x RCA L/R (amp in), 1 x RCA L/R (amp out), screw terminals (speakers) with 4 mm banana jack
Packing dimensions (W x H x L)	: 0.3 x 0.11 x 0.53 m
Gross weight	: 6.42 kg
Net weight	: 5.85 kg