

## NAUSB-3 - USB Chassis Connector



The NAUSB-3 is a reversible USB 3.0 feed-through adapter. The standardised D series body fits standard patch panels and provides additional protection for the plug-in connector.  
USB 3.0 feed-through panel jack

- Reversible adapter for feed-through direction: Type-A/B or Type-B/A
- Removable ground connection
- D series
- Complies with USB 3.0 specifications

## Technical data:

|                              |                                |
|------------------------------|--------------------------------|
| Description                  | : panel jack                   |
| Type                         | : NEUTRIK USB 3.0 feed-through |
| Quantity                     | : 1                            |
| Features                     | : USB Type-A/USB Type-B        |
| Colour/colour coding         | : nickel-plated                |
| Power rating                 | : -                            |
| Insulating resistance        | : -                            |
| Dielectric strength          | : -                            |
| Certification                | : -                            |
| Pole number                  | : -                            |
| Cable inlet                  | : -                            |
| Suitable cable cross section | : -                            |
| Connection                   | : 2 x USB                      |
| Strain relief                | : -                            |
| Cable bending protection     | : -                            |
| Stereo                       | : -                            |
| Mono                         | : -                            |
| Switches                     | : -                            |
| Material                     | : -                            |
| Central fixing               | : -                            |
| Contact type                 | : -                            |
| No. of contacts              | : -                            |
| Contact width                | : -                            |
| Contact distance             | : -                            |
| Admiss. ambient temp.        | : -25-+85 °C                   |
| Dimensions                   | : -                            |
| Diameter                     | : -                            |
| Length                       | : -                            |
| Weight                       | : 34 g                         |
| Other features               | : reversible insert            |