

PA-4000RC - PA Desk Microphone



PA 4-zone paging desktop microphone,
for connection to PA-40120 and PA-6040MPX.

- Selection buttons for 4 zones, for activating one or several zones
- ALL CALL button for activating all of the 4 zones
- Autom. chime via microphone announcement button (talk)
- LED status indication for the zone buttons (busy, emergency), power, mic fault, signal and talk
- Built-in gooseneck electret microphone
- Adjustable microphone sensitivity
- Chime can be activated or deactivated as required
- 24 V power supply via PA-40120 or PA-6040MPX
- Two RJ45 jacks for connection to PA-40120, PA-6040MPX or optional power supply and additional microphones PA-4000RC
- Supplied with connection module for PA-40120 and PA-6040MPX
- Up to 32 x PA-4000RC can be connected to PA-40120 or PA-6040MPX via bus
- Supplied with 3 m connection cable (Cat. 5e)

Technical data:

| | |
|--------------------------------|--|
| Description | : PA desktop microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : - |
| System | : - |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : via PA-40120, PA-6040MPX or optional 24 V power supply |
| Operating time | : - |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 0.9 kg |
| Cable | : Cat. 5e, 3 m |
| Connection | : 2 x RJ45 |
| Packing dimensions (W x H x L) | : 0.16 x 0.18 x 0.375 m |
| Gross weight | : 1.202 kg |
| Net weight | : 0.9 kg |