-

Technical data:

Bridged operation	: 1
Peak output power	: 1,800 W
Power rating	: 1,280 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 8 x 160 W
Power rating at 8 Ohm	: 8 x 100 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: 4 x 320 W
Output impedance	: -
Channels	: 8
Zones	: -
Inputs	: 0.7Â V/20Â kOhm
Attenuation factor	:
Frequency range	: 12-20,000 Hz
Crossover network	: yes
Crossover frequency	: 240 Hz
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: ? 60 dB
THD	: < 0.1%
Phantom power	: -
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 2,400 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm

Height	: 132 mm
Depth	: 310 mm
Rack units, RU	: 3
Weight	: 16.6 kg
Connections	: 8 x 3-pole XLR, bal.8 x screw terminal
Packing dimensions (W x H x L)	: 0.52 x 0.23 x 0.43 m
Gross weight	: 17.92 kg
Net weight	: 16.68 kg