-

Technical data:

Fanless	: 1
Bridged operation	: 1
Peak output power	: 600 W
Power rating	: 400 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 8 x 50 W
Power rating at 8 Ohm	: 8 x 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: 4 x 100 W
Output impedance	: -
Channels	: 8
Zones	: -
Inputs	: 1Â V/20Â kOhm unbal.550Â mV/20Â kOhm bal.
Attenuation factor	: -
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: ? 45 dB
THD	: -
Phantom power	: -
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 600 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -

Admiss. ambient temp.	: 0-40 °C

Width	: 483 mm
Height	: 90 mm
Depth	: 330 mm
Rack units, RU	: 2
Weight	: 10.5 kg
Connections	: 8 x XLR, bal. 8Â x RCA 8Â x spring-load. speaker term. L/R
Packing dimensions (W x H x L)	: 0.41 x 0.16 x 0.56 m
Gross weight	: 13.22 kg
Net weight	: 10.68 kg