

## SPE-230/WS - Loudspeaker Pair



**Indbygningshøjttalere, sæt, coaxialt system, 8 Ohm, diskant med ferrofluid.**

- Fugtbestandig
- Udført i hvid plastik i et stykke og med plastikmembran
- Alsidige anvendelsesmuligheder, fx i bilen, til PA-brug, på terrassen eller skibet

## Technical data:

Impedance (Z)	: 8 Ohm
Transmission technology	: -
Frequency range	: 100-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 25 W
Peak music power output (MAX)	: 50 W
SPL	: 85 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: $\varnothing$ 110 mm
Mounting depth	: 50 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\varnothing$ 150 mm x 66 mm
Outside diameter	: $\varnothing$ 150 mm

Width	: Å~ 150 mm
Height	: -
Depth	: 66 mm
Colour	: white
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.5 kg
Packing unit	: 2
Type of speaker	: 130
Packing dimensions (W x H x L)	: 0.165 x 0.08 x 0.33 m
Gross weight	: 1.33 kg
Net weight	: 1.145 kg
Outdoors	: 1
Low-impedance	: 1