


## PA-704 - PA Amplifier

100V 4Ω 8Ω 16Ω new



### Mono PA mixing amplifier

- 1 x 35 W
- 2 low-impedance microphone inputs
- 1 aux input, 1 phono input
- Speaker outputs via screw terminal contacts
- Input and output level controls
- 2-way tone control for the output
- Connection for a microphone talk button to switch off the other sources during announcements
- Mains operation and 12-24 V emergency power operation

## Technical data:

100 V	: 1
Low-impedance	: 1
Peak output power	: 70 W
Power rating	: 35 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 4
Zones	: -
Inputs	: 5 mV (mic), 210 mV (aux), 5 mV (phono)

Attenuation factor	: -
Frequency range	: 100-18,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: $\pm 10$ dB/150 Hz
Equalizer midrange	: -
Equalizer treble	: $\pm 10$ dB/6 kHz
S/N ratio	: ? 55 dB
Crosstalk attenuation	: -
THD	: < 1%
Phantom power	:
Mains voltage	: $\sim$ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 100 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 12-24 V

Power supply (possible  
alternative)  
Admiss. ambient temp.

: DC 2.5 A

: 0-40 °C

**MONACOR**



Width	: 320 mm
Height	: 85 mm
Depth	: 230 mm
Rack units, RU	: -
Weight	: 4.97 kg
Connections	: 2 x 6.3 mm jack (mic), 1 x RCA L/R (aux), 1 x RCA L/R (phono), screw contacts (speakers)

Packing dimensions (W x H x L)	: 0.37 x 0.14 x 0.28 m
Gross weight	: 5.33 kg
Net weight	: 4.97 kg