

## AKB-60 - Amplifier Module

60  
W<sub>RMS</sub>



### Aktivt højttalermodul, mono, 45 Wrms ved 4 Ohm

- Aktivt modul til brug med passive højttalere
- Til montering fx på bagsiden af passive højttalere
- Line-indgang via XLR eller phono
- Justerbar master-udgang
- Velegnet som måleforstærker til akustik-analysatorer
- Blæserfrit kølesystem med stort kølelement

## Technical data:

Low-impedance	: 1
Fanless	: 1
Peak output power	: 60 W
Power rating	: 45 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 45 W
Power rating at 8 Ohm	: 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 0.4 V/20 kOhm bal., 11 kOhm unbal.
Attenuation factor	: -
Frequency range	: 15-50,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: -
THD	: < 0.01%
Phantom power	: -
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 90 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C



Width	: 212 mm
Height	: 52 mm
Depth	: 190 mm
Rack units, RU	: -
Weight	: 2.2 kg
Connections	: 1 x XLR input, bal., 1 x RCA L/R (input), speaker cable (4-8 Ohm)
Packing dimensions (W x H x L)	: 0.235 x 0.105 x 0.315 m
Gross weight	: 2.6 kg
Net weight	: 2.216 kg