

WSA-24T - Wireless Speaker Adaptor



Trådløs stereosender, 2.4 GHz, til lydstreaming.

- Passer til modtager WSA-24R
- Stereo/mono switch
- LED-indikator for status og peak
- Ingen interferens takket være FHSS teknologien (Frequency Hopping Spread Spectrum)
- Analog line-indgang, 6,3 mm jackstik L/R og 3-polet XLR L/R
- Metalkabinet
- Strømforsyning medfølger

SOUNDCHECK 02/2016

"All too typical for IMG STAGELINE: the requirements of stage applications are effectively implemented."

tools4music 01/2016

"This compact solution is an excellent aid for every audio supplier ... shows itself ... as a robust and easy-to-use solution for audio streaming."

Technical data:

| | |
|--------------------|---|
| Frequency range | : 20-20,000 Hz |
| THD | : < 0.3% |
| Channel separation | : ± 90 dB |
| S/N ratio | : - |
| Transmitting power | : - |
| WLAN | : - |
| Bluetooth | : - |
| Operating range | : ? 30 m, without any obstacles |
| Profiles | : - |
| Codecs | : - |
| Power supply | : via incl. power supply |
| Width | : 130 mm |
| Height | : 54 mm |
| Depth | : 130 mm |
| Weight | : 470 g |
| Connections | : Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue |
| Other features | : 2.4 GHz, 25 channels, latency: 18Â ms |