

## TXS-606DT/2 - Microphone Transmitter



Wireless desktop microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Electret microphone cartridge, cardioid polar pattern
- 350 mm gooseneck, removable
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

## Technical data:

Multifrequency	: 1
Description	: microphone desk stand transmitter
Version	: -
Transmission method	: wireless
Polar pattern	: cardioid
System	: electret
Carrier frequency range	: 672.000-691.975 MHz
Transmitting power	: 25Â mW/2.5Â mW
Power supply	: 2 x 1.5 V batt. AA size
Operating time	: ? 8 h
Audio frequency range	: 30-18,000 Hz
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 120 x 65 x 178 mm (w/o gooseneck)
Weight	: 1.2 kg
Cable	: -
Connection	: -
Packing dimensions (W x H x L)	: 0.175 x 0.085 x 0.515 m
Gross weight	: 1.677 kg
Net weight	: 1.296 kg