

## TXS-611SET - Wireless Microphone



**Multifrekvens mikrofonsystem, med UHF PLL teknologi.**

- 1 trådløs mikrofon (cardioid karakteristik), 1 modtager, 1 strømforsyning
- Ægte diversity system
- 80 UHF kanaler (863-865 MHz)
- ACT funktion for transmission af den valgte frekvens til den trådløse mikrofon via infrarødt signal
- Automatisk søgning
- Volumen- og squelchkontrol
- Sendestyrke kan justeres på den trådløse mikrofon (høj/lav)
- Indikator for kanal, antenne A/B, ACT status og AF lydstyrke (modtager), kanal og batteristatus (trådløs mikrofon)
- Robust metalkabinet (modtager)

**Licensfrit i EU.**

## Technical data:

|                            |   |
|----------------------------|---|
| Multifrequency             | : 1   |
| Hand-held microphone       | : 1   |
| General information        | :   |
| Description                | : wireless microphone system                      |
| Carrier frequency range    | : 863-865 MHz                                     |
| Audio frequency range      | : 50-18,000 Hz                                    |
| Channels                   | : 1   |
| THD                        | : < 0.5%  |
| Dynamic range              | : 120 dB  |
| Latency                    | :   |
| RF S/N ratio               | : 105 dB  |
| Operating time             | : -   |
| Admiss. ambient temp.      | : 0-40 °C   |
| Power supply               | : -   |
| Dimensions                 | : -   |
| Total weight               | : -   |
| Connections                | : -   |
| Specifications transmitter | :   |
| Transmitting power         | : < 10 mW   |
| Operating range            | : $\hat{30}$ m                                    |
| Power supply transmitter   | : 2 x 1.5 V batt. AA size                         |
| Width transmitter          | : 52 mm   |
| Height transmitter         | : 52 mm   |
| Depth transmitter          | : 275 mm  |
| Weight transmitter         | : 235 g   |
| Connections transmitter    | : -   |
| Specifications receiver    | :   |
| Audio signal receiver      | : 350 mV/10 kOhm (jack) 25 mV/10 kOhm (XLR, bal.) |
| Power supply receiver      | : via encl. plug-in power supply                  |
| Width receiver             | : 152 mm  |
| Height receiver            | : 38 mm   |
| Depth receiver             | : 120 mm  |
| Weight receiver            | : 482 g   |
| Connections receiver       | : 1 x 6.3 mm jack, unbal. 1 x XLR, bal.           |