

## ECM-302B - Boundary Microphone



### Grænseflademikrofon

- Kan tilsluttes direkte til en phantom strømforsyning 9-48 V
- Transformerbalanceret AF udgang
- 6 m kabel og 3-polet mini XLR/XLR

**ECM-302B = sort**

**ECM-302B/WS = hvid**

## Technical data:

|                                |                             |
|--------------------------------|-----------------------------|
| Description                    | : boundary microphone       |
| Version                        | : -                         |
| Transmission method            | : cable                     |
| Polar pattern                  | : semi-cardioid             |
| System                         | : electret                  |
| Carrier frequency range        | : -                         |
| Transmitting power             | : -                         |
| Power supply                   | : -                         |
| Operating time                 | : -                         |
| Audio frequency range          | : 30-20,000 Hz              |
| Nominal impedance              | : 250 Ohm                   |
| Sensitivity                    | : 22 mV/Pa                  |
| S/N ratio                      | : -                         |
| Max. sound pressure            | : 140 dB                    |
| Power supply                   | : DC 17-48 V, phantom power |
| Gooseneck length               | : -                         |
| Housing material               | : -                         |
| Admiss. ambient temp.          | : 0-40 °C                   |
| Dimensions                     | : Å~ 120 mm x 22 mm         |
| Weight                         | : 350 g                     |
| Cable                          | : 6 m                       |
| Connection                     | : 3-pole mini XLR/XLR       |
| Packing dimensions (W x H x L) | : 0.135 x 0.055 x 0.125 m   |
| Gross weight                   | : 0.661 kg                  |
| Net weight                     | : 0.484 kg                  |