

SP-17/4 - Universal Loudspeaker



Universal speaker, 30 W, 4 Ohm

- For general applications and replacement purposes
- High power capability
- To be used in the bass-midrange

Technical data:

| | |
|-------------------------------------------|---------------------------------|
| Impedance (Z) | : 4 Ohm |
| Transmission technology | : - |
| Frequency range | : f3-6,000 Hz |
| Resonant frequency (fs) | : - |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : - |
| Power rating (RMS) | : 30 W |
| Peak music power output (MAX) | : 60 W |
| SPL | : 89 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : - |
| Moving mass (Mms) | : - |
| Mech. Q factor (Qms) | : - |
| Electr. Q factor (Qes) | : - |
| Total Q factor (Qts) | : - |
| Equivalent volume (Vas) | : - |
| DC resistance (Re) | : - |
| Force factor (BxL) | : - |
| Voice coil induct. (Le) | : - |
| Voice coil diameter | : - |
| Voice coil former | : - |
| Linear excursion (X _{MAX}) | : - |
| Eff. cone area (Sd) | : - |
| Magnet weight | : - |
| Magnet diameter | : $\tilde{\sim}$ 100 mm |
| Mounting cutout | : $\tilde{\sim}$ 147 mm |
| Mounting depth | : 71 mm |
| Mounting hole diameter | : $\tilde{\sim}$ 160 mm |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : $\tilde{\sim}$ 169 mm x 79 mm |
| Outside diameter | : $\tilde{\sim}$ 169 mm |

| | |
|--------------------------------|-------------------------|
| Width | : Å~ 169 mm |
| Height | : - |
| Depth | : 79 mm |
| Colour | : black |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 1.086 kg |
| Packing unit | : 1 |
| Type of speaker | : 6.5" |
| Packing dimensions (W x H x L) | : 0.17 x 0.085 x 0.17 m |
| Gross weight | : 1.13 kg |
| Net weight | : 1.086 kg |
| Low-impedance | : 1 |