
-

Technical data:

Impedance (Z)	: 8 Ohm
Transmission technology	: -
Frequency range	: fx-20 kHz
Resonant frequency (fs)	: 2.2 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 4,000 Hz
Power rating (RMS)	: 25 W
Peak music power output (MAX)	: 50 W
SPL	: 100 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: 40°/90°
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: \tilde{A} 25 mm
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: \tilde{A} 70 mm
Mounting cutout	: 120 x 70 \hat{A} mm
Mounting depth	: 65 mm
Mounting hole diameter	: -
Hole spacing X-axis	: 70 mm
Hole spacing Y-axis	: 131 mm
Dimensions	: 148.5 x 87.5 x 64 mm
Outside diameter	: -

Width	: 148.5 mm
Height	: 87.5 mm
Depth	: 46 mm
Colour	: black
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.5 kg
Packing unit	: 1
Type of speaker	: -
Packing dimensions (W x H x L)	: 0.15 x 0.07 x 0.09 m
Gross weight	: 0.554 kg
Net weight	: 0.498 kg
Low-impedance	: 1