

## ECM-402L - Electret Microphone



**Elektret knaphulsmikrofon, miniudgave.**

- Mikrofonkapsel med cardioid karakteristik
- Aftagelig clip og 1,2 m tilslutningskabel
- 3-polet mini XLR hunstik for tilslutning til valgfri phantom strømforsyningsadapter (EMA-300P) eller lommeseender TXS-...HSE

## Technical data:

Description	: tie clip microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 70-15,000 Hz
Nominal impedance	: 1.5 kOhm
Sensitivity	: 7 mV/Pa
S/N ratio	: -
Max. sound pressure	: 120 dB
Power supply	: via power supply adapter
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: Å~ 7 mm x 22 mm
Weight	: 4 g
Cable	: 1.2 m
Connection	: 3-pole mini XLR
Packing dimensions (W x H x L)	: 0.035 x 0.14 x 0.065 m
Gross weight	: 0.045 kg
Net weight	: 0.02 kg