

## ECM-501L/SK - Electret Microphone



### Elektret knaphulsmikrofon

- Sidder diskret på grund af den beige farve og størrelsen
- Mikrofonkapsel i høj kvalitet med omnidirectional karakteristisk
- Aftagelig clip og 1,2 m kabel
- 3-polet mini XLR for tilslutning til phantom strømforsyning (EMA-1, EMA-300P) eller lommeseender TXS-...HSE

## Technical data:

Description	: tie clip microphone
Version	: -
Transmission method	: cable
Polar pattern	: omnidir.
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 1 kOhm
Sensitivity	: 5.6 mV/Pa
S/N ratio	: -
Max. sound pressure	: 110 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: Å~ 5 mm x 10 mm
Weight	: 5 g
Cable	: 1.2 m
Connection	: 3-pole mini XLR
Packing dimensions (W x H x L)	: 0.065 x 0.14 x 0.035 m
Gross weight	: 0.035 kg
Net weight	: 0.012 kg