

PSUB-12AKA - Active Subwoofer



De kompakte subwoofere med indbyggede 2.1 aktive moduler med høj ydeevne er egnet til mange formål. De kan udgøre grundlaget for små eller mellemstore kompakte PA-systemer - uden yderligere forstærkere. Mikrofon- og lineindgange kan mixes, og delefrekvensen til subwoofer og de passive satellithøjtalere er justerbar. Det mixede signal kan videresendes til andre systemer via stereo pre out. **Aktiv 2.1 PA subwoofer, 1.200 W**

- Aktiv basrefleks-subwoofersystem i trækabinet
- Indbygget 2.1 aktivt modul
- Effekt: SUB: 500 W, SAT: 2 x 150 W
- 30 cm (12") basenhed med høj effekt og long excursion
- Stereo line- og mic-indgang med gain kontrol
- Justerbar delefrekvens: 80-250 Hz
- 2-vejs tonekontrol til bas og diskant, balance
- Indbygget limiter, clip indikator
- Udførelse i høj kvalitet, indbyggede bærehåndtag
- Frontgitter i metal, flange til montering på stativ, gummifødder

tastenwelt 03/2013

"The small active system (PSUB-12AKA & 2 x PAB-306/SW) can be used for general applications, suitable for entertainers, smaller DJ events or piano bars. Beside its transparent sound, the system impresses by a good workmanship and its features."

+ Good price-performance ratio **tools4music 01/2014**

"Provides a highly appealing sound. The PSUB-12AKA delivers a performance which perfectly matches the

top parts of the MOVE-06. Very compact size yet of a high power capability with a well-tuned sound. In a word: enjoyable!"

Technical data:

| | |
|--------------------------------|---------------------------------|
| active | : 1 |
| Active/passive | : active |
| Transmission technology | : cable |
| Total output power | : 1,200 W |
| Power rating (RMS) | : 500 W (SUB), 2 x 150 W (SAT) |
| Total power rating | : - |
| Power rating (RMS) | : - |
| Impedance | : - |
| Frequency range | : 30-250 Hz |
| THD | : - |
| S/N ratio | : ? 74 dB |
| Input signal | : 880 mV-7 V (line) 30 mV (mic) |
| System | : bass-reflex |
| Full range speaker | : - |
| Bass speaker | : 30 cm (12") bass speaker |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : 30 cm (12") |
| SPL | : - |
| Max. rated SPL | : 123 dB |
| Radiation angle/beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : wood |
| Colour | : black |
| Mounting device | : stand sleeve |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/1,870 VA |
| Dimensions | : 460 x 380 x 455 mm |
| Width | : 460 mm |
| Height | : 380 mm |

| | |
|--------------------------------|---|
| Depth | : 455 mm |
| Weight | : 28 kg |
| Inputs | : XLR L/R, bal. RCA L/R, unbal. 6.3 mm jack, unbal. |
| Outputs | : RCA L/R NEUTRIK SPEAKON L/R (sat > 150 Hz) |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.58 x 0.5 x 0.58 m |
| Gross weight | : 32.98 kg |
| Net weight | : 28.33 kg |