

---

-

## Technical data:

active	: 1
Active/passive	: active
Transmission technology	: cable
Total output power	: 1,100 W
Power rating (RMS)	: 550 W (400+150) bass: 400 W mid-high range: 150 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 35-20,000 Hz
THD	: < 0.06% (sub) < 0.07% (sat)
S/N ratio	: -
Input signal	: 400 mV/21 kOhm (line), 400 mV/12 kOhm (aux)
System	: full range
Full range speaker	: -
Bass speaker	: 30 cm (12")
Midrange speaker	: 6 x 7.6 cm (3")
Tweeter	: 2 x 2.5 cm (1")
Number of speakers	: 9
Speaker size	: -
SPL	: 98 dB/W/m
Max. rated SPL	: 122 dB
Radiation angle/beam angle	: hor.: 120°, vert.: 30°
Radiation angle, horizontal	: 120°
Radiation angle, vertical	: 30°
Features	: -
Housing material	: wood
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/760 VA
Dimensions	: 110 x 720 x 145 mm (column module) 345 x 520 x 450 mm (subwoofer)
Width	: -

Height

: -

---

Depth	: -
Weight	: 30 kg
Inputs	: 1 x XLR (line) 1 x RCA (L/R)
Outputs	: 1 x XLR, par. out
Replacement voice coil	: -
Other features	: -
Accessories	: mains cable, tripod pole, Speakon cable
Packing dimensions (W x H x L)	: 0.78 x 0.81 x 0.44 m
Gross weight	: 32.1 kg
Net weight	: 28.3 kg