


WALL-06T/WS - PA Speaker Cabinet



Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ohm operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Technical data:

| | |
|--------------------------------|-------------------------------------|
| Outdoors | : 1 |
| 100 V | : 1 |
| Low-impedance | : 1 |
| Active/passive | : passive |
| Transmission technology | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 100 W |
| Power rating (RMS) | : 32/16/8/4 W (100 V) 50 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 70-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : 16 cm (6") bass-midrange speaker |
| Midrange speaker | : - |
| Tweeter | : 25 mm (1") dome tweeter |
| Number of speakers | : 2 |
| Speaker size | : 6" |
| SPL | : 90 dB/W/m |
| Max. rated SPL | : 106 dB |
| Radiation angle/beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP65 |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 196 x 303 x 250 mm (with bracket) |

| | |
|--------------------------------|------------------------------|
| Width | : 196 mm |
| Height | : 303 mm |
| Depth | : 250 mm |
| Weight | : 3.5 kg |
| Inputs | : spring-load. speaker term. |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : for pivoting and tilting |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.23 x 0.33 x 0.505 m |
| Gross weight | : 7.63 kg |
| Net weight | : 6.97 kg |