
-

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
protected against ball rebound	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 240 W
Power rating (RMS)	: 120/60/30 W
Impedance	: 8 Ohm
Frequency range	: 50-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way coaxial
Full range speaker	: -
Bass speaker	: 20 cm (8") PA coaxial
Midrange speaker	: -
Tweeter	: 25 mm (1") horn tweeter
Number of speakers	: 2
Speaker size	: 20 cm (8")
SPL	: 96 dB/W/m
Max. rated SPL	: 117 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP45
Admiss. ambient temp.	: -30 °C to +40 °C

Power supply	: -
Dimensions	: 280 x 280 x 270 mm
Width	: 280 mm
Height	: 280 mm
Depth	: 270 mm
Weight	: 9.5 kg
Inputs	: 1 x NEUTRIK SPEAKON, screw terminal
Outputs	: 1 x NEUTRIK SPEAKON, par. out
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.33 x 0.37 x 0.33 m
Gross weight	: 11.64 kg
Net weight	: 10.76 kg