


ESP-232/SW - PA Speaker Cabinet



Vejrbestandigt 2-vejs PA væghøjttalersystem

- 100 V PA højttalere med fremragende lyd
- 13 cm polypropylen bas/mellemtonehøjttaler og dome tweeter
- 4 tapsætninger
- 8 Ohm og 100 V omskifter
- Høj effektivitet for så kompakt en højttaler
- Fås i sort (SW) eller hvid (WS) plastik med lakeret aluminiumsfrontgitter i samme farve; moderne design
- Vægbeslag i metal medfølger

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 50 W
Power rating (RMS)	: 30/20/10/5 W (100Â V) 25 W (8Â Ohm)
Impedance	: 8 Ohm
Frequency range	: 75-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: 13 cm
SPL	: 89 dB
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: IP55
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -



Dimensions	: 160 x 260 x 180 mm
Width	: 160 mm
Height	: 260 mm
Depth	: 180 mm
Weight	: 2.3 kg
Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.205 x 0.19 x 0.3 m
Gross weight	: 2.82 kg
Net weight	: 2.46 kg