

## MMX-602/SW - Mixer



**Mikrofon linemixer, 6 kanaler.**

- 6 stereo line-/monomikrofonindgange
- Justerbar automatisk talkover (-12 dB), kan vælges til kanal 1 eller kanal 1+2
- Balance for hver stereoindgang
- 3-vejs equalizer
- +12 V phantom strømforsyning
- LED VU meter, peak LED
- Master udgang og record udgang
- Udgang med stereo/mono omskifter
- Justerbar hovedtelefonudgang
- 482 mm (19") rack installation, 1 U

## Technical data:

Input channels	: 6
Number of mix/mono	: 6
No. of stereo	: 6
No. of channels	: -
No. of inputs	: -
Mic input	: 1 $\hat{A}$ mV/6.6 $\hat{A}$ kOhm, 6 x 3-pole XLR, bal.
Line input	: 100 $\hat{A}$ mV/10 $\hat{A}$ kOhm, 6 x RCA L/R
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 $\hat{A}$ V/600 $\hat{A}$ Ohm, 1 x RCA L/R 1 x 3-pole XLR L/R, bal.
Record output	: 310 $\hat{A}$ mV/600 $\hat{A}$ Ohm, 1 x RCA L/R
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: ? $\hat{A}$ 8 $\hat{A}$ Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: -
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.1%
S/N ratio	: 62 $\hat{A}$ dB, unweighted
Crosstalk	: -
Equalizer bass	: $\pm$ 12 $\hat{A}$ dB/50 $\hat{A}$ Hz
Equalizer midrange	: $\pm$ 12 $\hat{A}$ dB/1 $\hat{A}$ kHz
Equalizer treble	: $\pm$ 12 $\hat{A}$ dB/10 $\hat{A}$ kHz
equalizer	: -

Talkover	: -12 dB, manual
Phantom power	: -
Crossfader	: -
Media player	: -
Amplifier	: -
Power supply	: &acd; 230Â V/50Â Hz/12Â VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 12 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 47 mm
Depth	: 208 mm
Rack units, RU	: 1
Weight	: 2.8 kg
Packing dimensions (W x H x L)	: 0.25 x 0.09 x 0.53 m
Gross weight	: 3.76 kg
Net weight	: 2.985 kg