
SP-39 - Speaker



Headphone speaker, 32 Ohm

- For production of headphones, headsets
- For low-level signal processing

MONACOR

Technical data:

Impedance (Z)	:	32 Ohm
Transmission technology	:	-
Frequency range	:	f3-20,000 Hz
Resonant frequency (fs)	:	-
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	:	-
Power rating (RMS)	:	-
Peak music power output (MAX)	:	0.1 W
SPL	:	100 dB/1 V/0.01 m
Max. rated SPL	:	-
Max. voltage	:	-
Radiation angle	:	-
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Suspension compl. (Cms)	:	-
Moving mass (Mms)	:	-
Mech. Q factor (Qms)	:	-
Electr. Q factor (Qes)	:	-
Total Q factor (Qts)	:	-
Equivalent volume (Vas)	:	-
DC resistance (Re)	:	-
Force factor (BxL)	:	-
Voice coil induct. (Le)	:	-
Voice coil diameter	:	-
Voice coil former	:	-
Linear excursion (X_{MAX})	:	-
Eff. cone area (Sd)	:	-
Magnet weight	:	-
Magnet diameter	:	-
Mounting cutout	:	Ã˜ 40 mm
Mounting depth	:	-
Mounting hole diameter	:	-
Hole spacing X-axis	:	-
Hole spacing Y-axis	:	-
Dimensions	:	Ã˜Â 40Â mmÂ xÂ 8Â mm
Outside diameter	:	Ã˜ 40 mm

Width	: Ã˜ 40 mm
Height	: -
Depth	: 8 mm
Colour	: black/transparent
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.011 kg
Packing unit	: 1
Type of speaker	: -
Packing dimensions (W x H x L)	: 0.045 x 0.01 x 0.045 m
Gross weight	: 0.013 kg
Net weight	: 0.011 kg
Low-impedance	: 1