

BEE - USB Pro audio interface 2 kanaler



2-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB Type-C port, compatible with USB 3.0, (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- Sampling rate: up to 192 kHz max., 24 bits
- 2 mono input channels via comb. jacks (XLR/6.3 mm jack), balanced, switchable line/instrument
- Main output, switchable mono/stereo
- Low cut function
- Switchable direct monitoring
- 1 x 6.3 mm jack output L/R
- Adjustable 6.3 mm headphone output
- +48 V phantom power, can be activated for each channel
- LED peak indication for each channel
- Robust metal housing of compact size, brushed aluminium front panel, black anodised
- Separate USB Type-C input, DC 5 V, for external power supply (not included in the scope of delivery)

System requirements: Windows 10/11, Mac OS, iOS, Linux

Technical data:

| | |
|--------------------|--|
| Input channels | : - |
| Number of mix/mono | : - |
| No. of stereo | : - |
| No. of channels | : 2 |
| No. of inputs | : 4 |
| Mic input | : 2.5 mV, 2 x comb. XLR/6.3 mm (line/mic), bal. 1.4 kOhm |
| Line input | : 19 mV, 2 x comb. XLR/6.3 mm (line/mic), bal. 10.5 kOhm (line)/500 kOhm (inst.) |
| CD input | : - |
| Phono input | : - |
| Tape (play) | : - |
| Aux input | : - |
| Insert input | : - |
| Effect return | : - |
| Master output | : 6.5 V max., 2 x 6.3 mm jack L/R |
| Record output | : - |
| Monitor output | : - |
| Booth output | : - |
| Aux output | : - |
| Insert output | : - |
| Effect send | : - |
| Control room | : - |
| Tape (rec) | : - |
| Headphones | : 1 x 6.3 mm jack |
| Gooseneck lamp | : - |
| WiFi | : - |
| USB | : yes, USB Type-C (compatible with USB 3.0), full-duplex |
| Bluetooth | : - |
| Frequency range | : 20-20,000 Hz |
| THD | : 0.001% |
| S/N ratio | : ≥ 87 dBu |
| Crosstalk | : ≥ 55 dB |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| equalizer | : - |

| | |
|--|-------------------------------------|
| Talkover | : - |
| Phantom power | : +48 V |
| Crossfader | : - |
| Media player | : - |
| Amplifier | : - |
| Power supply | : via USB interface DC 5 V/1,250 mA |
| Mains voltage | : - |
| Mains frequency | : - |
| Power consumption, operation | : - |
| Operating voltage (possible alternative) | : DC 5 V |
| Power supply (possible alternative) | : 1,250 mA |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 190 mm |
| Height | : 40 mm |
| Depth | : 117 mm |
| Rack units, RU | : - |
| Weight | : 717 g |
| Packing dimensions (W x H x L) | : 0.18 x 0.062 x 0.236 m |
| Gross weight | : 1.017 kg |
| Net weight | : 0.725 kg |