

# PA-1414MX - 10-Channel PA Pre-Amplifier



## 10-kanals PA-forforstærker

- 5 XLR indgange, mic/line
- 4 indgange, XLR mic/phono line
- 2 XLR master udgange
- 1 record udgang (master1, master2)
- Indgange med volumenkontrol og udgangsvælger (master1, master1+2, master2)
- Begge master udgange har 2-vejs tonekontrol
- Gongtaste med prioritet, mulighed for fjernbetjening, 2-toners eller 4-toners gong, sirene
- 1 push-to-talk tilslutning, RJ45, med prioritet (passer til PA-4000PTT)
- Low cut filter til hver mikrofonindgang
- Prioritet for kanaler 2-3
- Phantom strømforsyning til elektret mikrofoner kan tilsluttes XLR-indgangene
- Tilsluttes stikkontakt eller 24 V nødstrømforsyning

## Technical data:

|  |   |
|--|---|
| Peak output power                            | : -   |
| Power rating                                 | : -   |
| Power rating at 2 Ohm                        | : -   |
| Power rating at 4 Ohm                        | : -   |
| Power rating at 8 Ohm                        | : -   |
| Power rating at 16 Ohm                       | : -   |
| Power rating at 100 V                        | : -   |
| Power rating with 4 Ohm<br>bridged operation | : -   |
| Power rating with 8 Ohm<br>bridged operation | : -   |
| Output impedance                             | : -   |
| Channels                                     | : 10  |
| Zones  | : -   |
| Inputs                                       | : 2.5 mV, bal. (mic), 250 mV, bal. (line XLR), 250 mV,<br>unbal. (line RCA) |
| Attenuation factor                           | :   |
| Frequency range                              | : 20-20,000 Hz (-0.5 dB)  |
| Crossover network                            | : -   |
| Crossover frequency                          | : -   |
| Integrated limiter                           | : -   |
| Equalizer bass                               | : $\pm 10$ dB/100 Hz  |
| Equalizer midrange                           | : -   |
| Equalizer treble                             | : $\pm 10$ dB/10 kHz  |
| S/N ratio                                    | : ? 60 dB (mic), ? 75 dB (line)   |
| Crosstalk attenuation                        | : -   |
| THD  | : < 0.05%   |
| Phantom power                                | : -   |
| Mains voltage                                | : $\sim$ 230 V  |
| Mains frequency                              | : 50 Hz   |
| Power consumption, operation                 | : 15 VA   |
| Power consumption, standby                   | : -   |
| Standby current                              | : -   |
| Operating voltage (possible<br>alternative)  | : DC 24 V   |
| Power supply (possible<br>alternative)       | : DC 0.5 A  |

Admiss. ambient temp.

: 0-40 °C

Width

: 482 mm

Height

: 45 mm



**MONACOR**



|                                |  |
|--------------------------------|--|
| Depth                          | : 240 mm   |
| Rack units, RU                 | : 1  |
| Weight                         | : 2.5 kg   |
| Connections                    | : 9 x XLR (mic/line inputs), 4 x RCA L/R (line inputs), 1 x RJ45 (push-to-talk microphone), 2 x XLR (outputs), 1 x RCA L/R (record output) |
| Packing dimensions (W x H x L) | : 0.34 x 0.14 x 0.55 m   |
| Gross weight                   | : 3.61 kg  |
| Net weight                     | : 2.57 kg  |