

ULM-164/SW - Line Mixer



Universal line-mixer, 6 kanals.

- 6 stereo-/monoindgange
- 2 separate stereoudgange (master 1 via phono og 6,3 mm jack), 1 monoudgang
- 3-vejs equalizer
- LED VU meter, med omskifter for valg af udgang
- Clip LED for hver kanal
- Balancekontrol via centre click for stereo-indgangene
- Udvidet muting funktion
- Justerbar hovedtelefonudgang
- 482 mm (19") rack installation, 1 U

Technical data:

Input channels	: -
Number of mix/mono	: -
No. of stereo	: -
No. of channels	: 6
No. of inputs	: 12
Mic input	: -
Line input	: 150 mV/50 kOhm (stereo), 6 x RCA L/R 150 mV/25 kOhm (mono), 6 x 6.3 mm jack, unbal.
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 V/600 Ohm (stereo), 2 x RCA (1 x 6.3 mm) L/R 2 V/600 Ohm (mono), 1 x 6.3 mm jack
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 8 Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: -
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.05%
S/N ratio	: 69 dB, unweighted
Crosstalk	: -
Equalizer bass	: ± 12 dB/80 Hz
Equalizer midrange	: ± 12 dB/1 kHz
Equalizer treble	: ± 12 dB/10 kHz
equalizer	: -

Talkover	: -
Phantom power	: -
Crossfader	: -
Media player	: -
Amplifier	: -
Power supply	: ∿ 230Â V/50Â Hz/10Â VA
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 10 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 48 mm
Depth	: 175 mm
Rack units, RU	: 1
Weight	: 2.3 kg
Packing dimensions (W x H x L)	: 0.18 x 0.047 x 0.482 m
Gross weight	: 3.035 kg
Net weight	: 2.32 kg