

EPS110/RS485 - MP3 afspiller DIN



MP3 player,
event-driven.

- For mounting onto DIN rails according to DIN EN 60715, 2 HP
- For SDHC/SD/MMC cards up to 32 GB (FAT32), not included in the scope of delivery
- Extensive playback functions
- 7 binary inputs
- In/Out string triggers
- RS-485 interface for communication
- Decentral extensions
- Connection for EIB push-button sensor
- Balanced stereo line output, can also be used as a headphone output
- Delay function up to 60 seconds
- Free configuration software
- Firmware update possible

Technical data:

Description	: MP3 player
Media	: MP3, WAV
Frequency range	: 18-20,000 Hz
THD	: 0.001%
Channel separation	: -
Dynamic range	: -
S/N ratio	: -
Output, analogue	: 2 V/600Ω Ohm
Output, digital, U _{pp}	: -
Power supply	: -
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Operating voltage (possible alternative)	: 7-24 V
Power supply (possible alternative)	: 60 mA (7 V) 25 mA (24 V)
Admiss. ambient temp.	: -35-+55 °C
Dimensions	: 74 x 113 x 35 mm
Dim., player mech.	: -
Dim., control panel	: -
Weight	: 96 g
Connections	: 7 binary outputs
Packing dimensions (W x H x L)	: 0.037 x 0.095 x 0.075 m
Gross weight	: 0.1155 kg