# NAC-3FX-W-TOP - Powercon inline jack



NEUTRIK POWERCON True1 TOP inline jack

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ∿ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0
- Protection classs IP65

## Technical data:

| | | |
|---|---|---|
| Description | : | inline jack |
| Type | : | NEUTRIK POWERCON TOP |
| Quantity | : | 1 |
| Features | : | latching device |
| Colour/colour coding | : | black |
| Power rating | : | ∿Â 250Â V/16Â A |
| Insulating resistance | : | ? 100 MOhm |
| Dielectric strength | : | DC 4 kV/∿ 2.8 kV |
| Certification | : | UL, VDE |
| Pole number | : | 2+PE |
| Cable inlet | : | 6-12 mm |
| Suitable cable cross section | : | - |
| Connection | : | - |
| Strain relief | : | yes |
| Cable bending protection | : | - |
| Stereo | : | - |
| Mono | : | - |
| Switches | : | - |
| Material | : | silver-plated bronze contacts, plastic |
| Central fixing | : | - |
| Contact type | : | - |
| No. of contacts | : | - |
| Contact width | : | - |
| Contact distance | : | - |
| Admiss. ambient temp. | : | -30-+80 °C |
| Dimensions | : | Ã˜ 26.5 mm x 77-80 mm |
| Diameter | : | - |
| Length | : | - |
| Weight | : | 33 g |
| Other features | : | - |