

NAC3MPX-TOPSB - Powercon panel plug



NEUTRIK POWERCON True1 TOP Connectors

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ∿ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Robust version with latching device and cable inlet with self-adjusting clamps (plug and inline jack only)
- Self-extinguishing according to UL 94V-0
- Protection classs IP65 (NAC3FX-W-TOP and NAC3MX-W-TOP)

NEUTRIK POWERCON True1 TOP panel plug

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ∿ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0

Technical data:

Description	: panel plug
Type	: NEUTRIK POWERCON TOP
Quantity	: 1
Features	: latching device
Colour/colour coding	: black
Power rating	: ∿Â 250Â V/16Â A
Insulating resistance	: ? 100 MOhm
Dielectric strength	: DC 4 kV/∿ 2.8 kV
Certification	: UL, VDE
Pole number	: -
Cable inlet	: -
Suitable cable cross section	: -
Connection	: blade terminals, 6.35 mm
Strain relief	: -
Cable bending protection	: -
Stereo	: -
Mono	: -
Switches	: -
Material	: plastic
Central fixing	: -
Contact type	: -
No. of contacts	: 2
Contact width	: -
Contact distance	: -
Admiss. ambient temp.	: -30-+80 °C
Dimensions	: 26 x 31 x 38.2 mm
Diameter	: -
Length	: -
Weight	: 11 g
Other features	: -