

## TXS-606HT/2 - Handheld Transmitter



Hand-held microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

SOUNDCHECK 04/2012

"The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound."

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

## Technical data:

|                                |                                    |
|--------------------------------|------------------------------------|
| Multifrequency                 | : 1                                |
| Hand-held microphone           | : 1                                |
| Description                    | : hand-held microphone transmitter |
| Version                        | : -                                |
| Transmission method            | : wireless                         |
| Polar pattern                  | : cardioid                         |
| System                         | : dynamic                          |
| Carrier frequency range        | : 672.000-691.975 MHz              |
| Transmitting power             | : 25 mW/2.5 mW                     |
| Power supply                   | : 2 x 1.5 V batt. AA size          |
| Operating time                 | : ? 8 h                            |
| Audio frequency range          | : 30-18,000 Hz                     |
| Nominal impedance              | : -                                |
| Sensitivity                    | : -                                |
| S/N ratio                      | : -                                |
| Max. sound pressure            | : -                                |
| Power supply                   | : -                                |
| Gooseneck length               | : -                                |
| Housing material               | : -                                |
| Admiss. ambient temp.          | : 0-40 °C                          |
| Dimensions                     | : ~ 51 mm x 265 mm                 |
| Weight                         | : 312 g                            |
| Cable                          | : -                                |
| Connection                     | : -                                |
| Packing dimensions (W x H x L) | : 0.075 x 0.06 x 0.295 m           |
| Gross weight                   | : 0.461 kg                         |
| Net weight                     | : 0.323 kg                         |