

DRIVE-10A - PA DSP Loudspeaker





With the DRIVE series
you will get robust and easy-to-use PA speakers which are suitable for versatile applications and feature the latest DSP-controlled amplifier technology. There are 3 selectable presets available to provide a perfect sound adjustment for any kind of application. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.
Professional active DSP speaker system with 2-channel amplifier, 200 W

- Compact 10/2 full range system with cabinet made of birch plywood

- DSP-controlled 2-channel amplifier (bass: class D, tweeter: class A/B)
- 3 selectable presets

- FLAT (linear adjustment)
- MUSIC (slightly raised bass and treble)
- LOW CUT (with high-pass filter for application with an additional subwoofer)

- 25 cm (10") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°
- Excellent sound characteristics
- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation, stand sleeve
- Volume control
- 2 x balanced line in
- 2 x parallel line out
- 1 x balanced mix out
- Power and clip indicator

Technical data:

active	:	1
DSP	:	1
Active/passive	:	active
Transmission technology	:	cable
Total output power	:	400 W
Power rating (RMS)	:	DSP-controlled 200 W (140 + 60) bass: 140 W treble: 60 W
Total power rating	:	-
Power rating (RMS)	:	-
Impedance	:	-
Frequency range	:	55-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	790 mV/40 kOhm (line, bal.)
System	:	10/2 full range
Full range speaker	:	-
Bass speaker	:	25 cm (10") bass speaker
Midrange speaker	:	-
Tweeter	:	25 mm (1") horn tweeter
Number of speakers	:	2
Speaker size	:	25 cm (10")
SPL	:	98 dB/W/m
Max. rated SPL	:	123 dB
Radiation angle/beam angle	:	H: 90°/V: 60°, horn can be turned
Radiation angle, horizontal	:	90°
Radiation angle, vertical	:	60°
Features	:	-
Housing material	:	birch plywood
Colour	:	black
Mounting device	:	M8 threaded inserts, stand sleeve
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	∿ 230Â V/50Â Hz/350Â VA
Dimensions	:	320 x 530 x 350 mm
Width	:	320 mm

Height	: 530 mm
Depth	: 350 mm
Weight	: 12.18 kg
Inputs	: 1 x comb. XLR/6.3 mm: line 1 x XLR: line
Outputs	: 2 x XLR par. out 1 x XLR mix out
Replacement voice coil	: -
Other features	: DSP-controlled limiter 3 selectable presets
Accessories	: -
Packing dimensions (W x H x L)	: 0.42 x 0.63 x 0.45 m
Gross weight	: 16.02 kg
Net weight	: 12.18 kg