

DM-730S - Dynamic Microphone

new



Dynamic microphone,
for vocals (PA, stage, DJ).

- Supercardioid polar pattern
- Neodymium version
- Frequency range: 50-18,000 Hz
- Slide potentiometer
- Diecast zinc body
- Supplied with microphone holder, 9 mm (") adapter screw and microphone bag

Technical data:

| | |
|--------------------------------|-------------------------|
| Description | : vocal microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : supercardioid |
| System | : dynamic, neodymium |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 50-18,000 Hz |
| Nominal impedance | : 300 Ohm |
| Sensitivity | : 2.3 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : diecast zinc |
| Admiss. ambient temp. | : - |
| Dimensions | : ~ 48 mm x 182 mm |
| Weight | : 279 g |
| Cable | : - |
| Connection | : XLR, bal. |
| Packing dimensions (W x H x L) | : 0.26 x 0.07 x 0.125 m |
| Gross weight | : 0.58 kg |
| Net weight | : 0.342 kg |