ESP-1000AB - PA Wall-/Ceiling Speaker



PA A/B wall speaker,
with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille
- Supplied with aluminium mounting bracket, screws and wall plugs

Technical data:

100 V	:	1
EN 54 certification	:	1
Active/passive	:	passive
Transmission technology	:	100 V
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	-
Power rating (RMS)	:	2 x 6/3/1.5 W
Impedance	:	-
Frequency range	:	80-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	-
Full range speaker	:	2 x 10 cm
Bass speaker	:	-
Midrange speaker	:	-
Tweeter	:	-
Number of speakers	:	2
Speaker size	:	10 cm
SPL	:	92 dB/W/m
Max. rated SPL	:	100 dB
Radiation angle/beam angle	:	160°
Radiation angle, horizontal	:	160°
Radiation angle, vertical	:	160°
Features	:	-
Housing material	:	metal
Colour	:	white
Mounting device	:	bracket
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	-10 °C to +50 °C
Power supply	:	-
Dimensions	:	Ã˜Â 220Â mmÂ xÂ 100Â mm
Width	:	Ã˜ 220 mm

Height	:	-
Depth	:	100 mm
Weight	:	1.98 kg
Inputs	:	-
Outputs	:	-
Replacement voice coil	:	-
Other features	:	-
Accessories	:	-
Packing dimensions (W x H x L)	:	0.23 x 0.12 x 0.23 m
Gross weight	:	2.126 kg
Net weight	:	1.986 kg