

DA-P20-130/T - PA Loudspeaker



Weatherproof PA sound projector,
for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 13 cm waterproof full range speaker
- 100 V transformer with power taps 20/10/5/2.5 W
- Connection via ceramic terminal and thermal fuse in the junction box (cable length: 1 m)
- ABS plastic housing with front protective grille
- Robust aluminium mounting bracket

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
EN 54 certification	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 20/10/5/2.5 W
Impedance	: -
Frequency range	: 150-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: 13 cm
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: 13 cm
SPL	: 90 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle/beam angle	: 110°
Radiation angle, horizontal	: 110°
Radiation angle, vertical	: 110°
Features	: -
Housing material	: ABS plastic
Colour	: white
Mounting device	: bracket
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -20 °C to +90 °C
Power supply	: -

Dimensions	: 145 mm x 222 mm
Width	: 145 mm
Height	: -
Depth	: 222 mm
Weight	: 1.367 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.175 x 0.295 x 0.18 m
Gross weight	: 1.625 kg
Net weight	: 1.367 kg