# ATS-825C - Charger Case



Transport case with integrated charging function and programming function,
for transmitters and receivers from the ATS-80 series.

- For simultaneously charging rech. batteries of up to 25 devices
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Matrix LCD
- Transport case with carrying handle, lockable
- Supplied with matching power supply
- Supplied with programming software for ATS-80R and ATS-80T (SYNC function)

Supplied w/o devices.

# Technical data:

| | | |
|---|---|---|
| Description | : | transport case |
| Nominal value | : | 25 devices |
| Type | : | with charging function |
| Colour | : | black |
| Material | : | - |
| Suitable for | : | ATS-80R, ATS-80T |
| Power supply | : | via encl. power supply |
| Admiss. ambient temp. | : | 0-40 °C |
| Dimensions | : | 437 x 170 x 266 mm (charger only) |
| Length | : | - |
| Mounting dimensions | : | - |
| Weight | : | 5.3 kg |
| Connections | : | - |
| Other features | : | - |
| Packing unit | : | 1 |
| Packing dimensions (W x H x L) | : | 0.19 x 0.33 x 0.46 m |
| Gross weight | : | 6.15 kg |
| Net weight | : | 5.29 kg |