
-

Technical data:

Impedance (Z)	: 8 Ohm
Transmission technology	: -
Frequency range	: f3-2,500 Hz
Resonant frequency (fs)	: 40 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 1,000 W
Peak music power output (MAX)	: 2,000 W
SPL	: 96 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 0.10 mm/N
Moving mass (Mms)	: 153 g
Mech. Q factor (Qms)	: 3.98
Electr. Q factor (Qes)	: 0.36
Total Q factor (Qts)	: 0.33
Equivalent volume (Vas)	: 105 l
DC resistance (Re)	: 5.1 Ohm
Force factor (BxL)	: 23.53 Tm
Voice coil induct. (Le)	: 1.8 mH
Voice coil diameter	: \tilde{A} ~ 100 mm
Voice coil former	: glass fibre
Linear excursion (X _{MAX})	: \pm 8 mm
Eff. cone area (Sd)	: 855 cm ²
Magnet weight	: 3.1 kg
Magnet diameter	: \tilde{A} ~ 220 mm
Mounting cutout	: \tilde{A} ~ 351 mm
Mounting depth	: 168 mm
Mounting hole diameter	: \tilde{A} ~ 365-375 mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: \tilde{A} ~ 385 mm x 180 mm
Outside diameter	: \tilde{A} ~ 385 mm

Width	: Å~ 385 mm
Height	: -
Depth	: 180 mm
Colour	: black
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 10.26 kg
Packing unit	: 1
Type of speaker	: 15"
Packing dimensions (W x H x L)	: 0.43 x 0.21 x 0.43 m
Gross weight	: 11.88 kg
Net weight	: 10.26 kg
Outdoors	: 1
Low-impedance	: 1