
-

Technical data:

Impedance (Z)	: 8 Ohm
Transmission technology	: -
Frequency range	: fx-20,000 Hz
Resonant frequency (fs)	: 1.5 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 3.5 kHz
Power rating (RMS)	: 75 W
Peak music power output (MAX)	: 150 W
SPL	: 105 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: 40°/90°
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: \tilde{A} 34.5 mm
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: \tilde{A} 80 mm
Mounting cutout	: 237 x 83 mm
Mounting depth	: 220 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 268 x 112 x 210 mm
Outside diameter	: -

Width	: 268 mm
Height	: 112 mm
Depth	: 210 mm
Colour	: black
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.165 kg
Packing unit	: 1
Type of speaker	: -
Packing dimensions (W x H x L)	: 0.31 x 0.115 x 0.245 m
Gross weight	: 1.408 kg
Net weight	: 1.165 kg
Low-impedance	: 1
Replacement voice coil	: MHD-152/VC