-

Technical data:

Impedance (Z)	:	8 Ohm
Transmission technology	:	-
Frequency range	:	fx-22,000 Hz
Resonant frequency (fs)	:	3 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	:	5,000 Hz
Power rating (RMS)	:	50 W
Peak music power output (MAX)	:	100 W
SPL	:	110 dB/W/m
Max. rated SPL	:	-
Max. voltage	:	-
Radiation angle	:	60°/60°
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Suspension compl. (Cms)	:	-
Moving mass (Mms)	:	-
Mech. Q factor (Qms)	:	-
Electr. Q factor (Qes)	:	-
Total Q factor (Qts)	:	-
Equivalent volume (Vas)	:	-
DC resistance (Re)	:	-
Force factor (BxL)	:	-
Voice coil induct. (Le)	:	-
Voice coil diameter	:	Ã˜ 44.5 mm
Voice coil former	:	-
Linear excursion (X_{MAX})	:	-
Eff. cone area (Sd)	:	-
Magnet weight	:	-
Magnet diameter	:	Ã˜ 103 mm
Mounting cutout	:	Ã˜ 105 mm
Mounting depth	:	93 mm
Mounting hole diameter	:	-
Hole spacing X-axis	:	-
Hole spacing Y-axis	:	-
Dimensions	:	119 x 119 x 90 mm
Outside diameter	:	-

Width	: 119 mm
Height	: 119 mm
Depth	: 90 mm
Colour	: black/silver
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 2.6 kg
Packing unit	: 1
Type of speaker	: -
Packing dimensions (W x H x L)	: 0.125 x 0.11 x 0.13 m
Gross weight	: 2.65 kg
Net weight	: 2.58 kg
Low-impedance	: 1
Replacement voice coil	: MHD-540/VC