

STA-235 - Amplifier



Stereo PA-forstærker, med indbygget limiter.

- LCD-indikator for temperatur, mode og power
- Stereo eller brokobling
- Limiter funktion
- Temperaturstyret ventilator
- 2 x volumenkontrol
- Ground lift
- Højttalerforsinkelse
- Beskyttelseskredsløb med LED-indikator for beskyttelse mod kortslutning og overophedning
- Hver kanal har LED-indikator for overbelastning, volumen og signal

Technical data:

| | |
|--|-----------------|
| Bridged operation | : 1 |
| Peak output power | : 1,400 W |
| Power rating | : 1,000 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : 2 x 500 W |
| Power rating at 8 Ohm | : 2 x 400 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : 1 x 1,000 W |
| bridged operation | |
| Output impedance | : - |
| Channels | : 2 |
| Zones | : - |
| Inputs | : 1.2 V/10 kOhm |
| Attenuation factor | : - |
| Frequency range | : 10-50,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : yes |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 80 dB |
| Crosstalk attenuation | : ? 50 dB |
| THD | : < 0.1% |
| Phantom power | : - |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 2,000 W |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 482 mm |

| | |
|----------------|---|
| Height | : 100 mm |
| Depth | : 330 mm |
| Rack units, RU | : 2 |
| Weight | : 11.5 kg |
| Connections | : 1 x 3-pole XLR L/R, bal. 1 x 6.3 mm jack L/R, bal. 3 x SPEAKER 2 x pair of screw terminals |

| | |
|--------------------------------|------------------------|
| Packing dimensions (W x H x L) | : 0.37 x 0.14 x 0.51 m |
| Gross weight | : 13.52 kg |
| Net weight | : 12.6 kg |